

PHOENIX

DELTA EC



WEATHER PROOF PACK

TYPE: SIMPLEX

FORM: OUTDOOR

CONDENSER: INCLUDED

DESIGN

- Space saving stackable modules
- Weatherproof enclosure for easy outdoor installation
- Integrated electrical panel with controller

OPTIONS

- VSD smooths out power fluctuations and increases efficiency
- Soft starters to reduce the compressor starting current for gensets or solar systems.
- EC fan option for low-noise and floating head pressure savings

QUALITY

- Manufactured in either epoxy coated mild steel or stainless steel (3CR12)
- Manufactured under strict ISO9001 quality management
- PU coated condensers

VERSATILE

- Wide range to suit any application
- Ideal for both hermetic and semi hermetic compressors
- Custom-made options available

PACK TYPE	Fan Size (mm)	No. Fans	Approx. Weight (kg)	Approx. Size (mm)	Supply Voltage		
SINGLE	350, 400, 500	1	160 - 200	750 x 920 x 810	230-400V	Standard Semi-hermetic Range	2.9kW ↔ 108kW @ 0°C 2.3kW ↔ 90.9kW @ -5°C 1.9kW ↔ 76.3kW @ -10°C 0.6kW ↔ 27.8kW @ -32°C
DOUBLE	400, 500	2	350 - 400	1500 x 920 x 810	230-400V		
TRIPLE	500	3	400 - 600	2250 x 920 x 1250	230-400V		
MIDI	500	2	400 - 600	1500 x 920 x 1250	230-400V	Standard Hermetic Range	2.0kW ↔ 34kW @ 0°C 1.6kW ↔ 26.4kW @ -5°C 1.4kW ↔ 22kW @ -10°C 0.4kW ↔ 8.6kW @ -32°C
MAXI	500	4	600 - 800	1500 x 920 x 1620	230-400V		
ULTRA	500	6	800 - 1000	2250 x 920 x 1620	230-400V		
ULTRA TRIPLE	500	9	950 - 1250	2250 x 920 x 2430	230-400V		

